



» Stubble Mulching

McCONNEL FLEX WING

Machines Features:

- » 26'3" (8.0m) cutting widths
- » Self-levelling tongue and swivel clevis
60° of working range movement
- » Independently folding hydraulic wings
- » Heavy duty gearboxes
- » 1000rpm wide angle PTO
- » Slip clutch protection
- » All shaft drive
- » Five pan blade carriers
- » Four hardened updraft blades per rotor
- » Front and rear chain guards
- » Replaceable full length skids
- » Road lighting kit
- » Parking jack
- » Cutting heights from 1" - 1'2" (25mm - 356mm)
- » Maximum cutting diameter 2" (50mm)

Markets:

- » Agricultural
- » Governmental
- » Contractors

Tractor Requirement:

- » 120hp minimum tractor horse power
(dependent on model)

ЗАО МОСТ-ТЕХНИКА

121357. Москва
ул. Козлова 30
Тел. +7 (495) 775 0175
Факс: +7 (495) 775 0176
E-mail: info@most-technics.ru
Web: www.most-technics.ru



Airport maintenance



Pasture maintenance

Description		
Cutting width	Maximum width of cut	26'3" (8m)
HP requirement	Minimum HP requirement of tractor	120hp
Weight	Weight of machine	6,689lbs (3034kg)
Cutting height	Min to max cutting height	1" - 1'2" (25mm - 356mm)
Cutting capacity	Maximum diameter of material	2" (50mm)
Overall width	Maximum external width	26'9" (8.15m)
Overall length	Maximum external length	16'10" (5.13m)
Transport width	Width when folded for transport	9'9" (2.98m)
Transport height	Height when folded for transport	12'4" (3.76m)
PTO speed	max RPM of PTO Shaft	1,000rpm
Gearbox rating	Power Divide	220hp
	Centre Gearbox	800rpm
	Wing Gearboxes	974rpm outer, 812rpm inner
No of blades	Number of heat treated up draft blades	20
Tip Speed	Wings & Centre Deck	4682m per min
Rotor speed	Wings & Centre Deck	4614rpm
Blade overlap	Distance blades overlap when running	6" (154mm)
Hydraulic wing flex	Degrees of wing travel in work	90° up, 15° down
No of wheels	Number of wheels	8
Skid shoes	Replaceable skid shoes	Standard

SCHULTE FLEX WING MOWERS